



ENTRY POINT INTERNATIONAL LLC

Product Data Sheet

Ridiculous® FR Tape



TECHNICAL DATA

Material Construction:

Backing: Soft PVC
(Polyvinyl Chloride)
Adhesive: Natural Rubber/Resin

Description:

20 MIL Premium FR Tape

Intended Use:

Temporary Sealing or Joining of Entry Point Protection Products

Appearance:

Black

Unit:

Roll

Dimensions:

~3" x 33.3 yds

Thickness:

.50 mm

Weight:

~2 lbs

Stocking Units:

16 Roll Box

Tensile Strength:

32 inch/lbs

Storage Recommendations:

Store away from heat sources, open flames and strong acids and/or bases. Store indoors within recommended storage temperatures 10°C to 35°C / 50°F to 95°F. Keep out of direct sunlight. Store Flat.

Issue Date:

11/01/20

Revision Date:

11/01/20

PRODUCT DESCRIPTION

Ridiculous FR Tape is a Heavy Duty and flexible SPVC surface protection tape. Designed to meet the most demanding applications, it provides excellent abrasion, impact and rupture resistance, while also being able to withstand chemicals, water, mold, UV and other jobsite products that would destroy normal tape.

KEY FEATURES & BENEFITS

- 20 mil premium tape designed for both heavy-duty jobs and standard uses
- Highly conformable and resistant to aging, sun, water, fungus, bacteria, oil, acids, alkalis and corrosive chemicals
- Easy dispensing from the roll for sealing and joining Entry Point temporary protection components, but will require cutting due to high tear-reinforcement
- Allows for repeated bending and flexing as materials shift under load
- Tested in accordance with UL 510 Standard for Polyvinyl Chloride, Polyethylene and Rubber Insulating Tape for Flame Spread and Smoke Development
- Compliments the Fire-Retardant properties of the full line of Entry Point products

DATA

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Adhesion to Steel	11 oz/inch
Tensile Strength	32 lbs/inch
Elongation	300%
Flame Resistance Grade	UL510

Note: Refer to current [Installation Guide](#) for correct product usage.

DISCLAIMER

Information contained within this "Product Data Sheet" is for guidance only and intended for experienced industry professionals. As conditions of usage and installation are beyond our control, we do not warrant performance obtained. Information is given to the best of Entry Point International's knowledge, based on manufacturers input, laboratory testing and practical experience.

Entry Point INTERNATIONAL LLC
866-664-3129

www.entrypointusa.com