



# ENTRY POINT INTERNATIONAL LLC

## Product Data Sheet

### Absurd® FR Tape



#### TECHNICAL DATA

##### Material Construction:

Backing: PE Film  
Adhesive: Natural Rubber/Resin  
Reinforcement: PET Cloth

##### Description:

17 MIL Premium FR Tape

##### Intended Use:

Temporary Sealing or Joining of Entry Point Protection Products

##### Appearance:

Black

##### Unit:

Roll

##### Dimensions:

~2" x 35 yds (~48 MM X 32 M)

##### Thickness:

.432 mm (17.0)

##### Weight:

~1.6 lbs

##### Stocking Units:

12 Roll Box

##### Tensile Strength:

44 inch/lbs

##### Storage Recommendations:

Store away from heat sources, open flames and strong acids and/or bases. Store indoors within recommended storage temperatures 10°C to 35°C / 50°F to 95°F. Keep out of direct sunlight. Store Flat.

##### Issue Date:

11/01/20

##### Revision Date:

11/01/20

#### PRODUCT DESCRIPTION

Absurd FR Tape is a Polyethylene (PE) coated cloth tape with an aggressive pressure-sensitive natural rubber adhesive. Designed to meet demanding applications, it adheres well to a wide variety of surfaces under a broad range of temperature conditions.

#### KEY FEATURES & BENEFITS

- Easy dispensing from the roll for sealing and joining Entry Point temporary protection components, may require cutting due to enhanced reinforcement
- Compliments the Flame-Retardant properties of the full line of Entry Point products
- Tested in accordance with UL 723 for Flame Spread and Smoke Development
- Professional quality, ultra-tough, all weather and moisture resistant
- 17 mil premium tape designed for both heavy-duty jobs and standard uses
- 12% Elongation
- 100% Made in the USA

#### TEST DATA

GOVERNMENT CONFORMANCE: Tested in accordance with UL-723.

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

PSTC-101: Adhesion to Steel (oz/in of width) 60 (16.4 N/25mm)

PSTC-131: Tensile Strength (lbs/in of width) 44 (193 N/25mm)

PSTC-131: Elongation (% at break) 12

**Note: Refer to current [Installation Guide](#) for correct product usage.**

#### DISCLAIMER

Information contained within this "Product Data Sheet" is for guidance only and intended for experienced industry professionals. As conditions of usage and installation are beyond our control, we do not warrant performance obtained. Information is given to the best of Entry Point International's knowledge, based on manufacturers input, laboratory testing and practical experience.

**Entry Point** INTERNATIONAL LLC  
866-664-3129

[www.entrypointusa.com](http://www.entrypointusa.com)